

YILDIZ GEMİ A.Ş. / PERINI NAVI SRL

- C2086 S/Y ASAHI 56m (iskele-sancak *portside-starboardside*)
C2095 S/Y SALUTE 56m (iskele-sancak *portside-starboardside*)
C2106 S/Y SILVANA 56m (iskele-sancak *portside-starboardside*)
C2123 S/Y PANTHALASSA 56m (iskele-sancak *portside-starboardside*)
C2126 S/Y MELEK 56m (iskele-sancak *portside-starboardside*)
C2132 S/Y 56m (iskele-sancak *portside-starboardside*)



GENEL ÖZELLİKLER

- G 6640 mm - B 2650 Net Açıklık
- ABS / MCA onaylı
- Tık kaplamaya uygun yüzey menteşeler
- Hidrolik açma / kapama
- Hidrolik pençe kilitler
- Serpinti geçirmez tasarım
- Baskı tipi conta
- Her iki kapağı da kontrol eden ortak güç ünitesi
- Radyo kontrollü uzaktan kumanda
- 1 dakikalık açılma veya kapanma süresi

MALZEME BİLGİSİ

Kapak: Alüminyum
Kasa: Paslanmaz Çelik
Kilit ve Menteşeler: Paslanmaz Çelik

AĞIRLIK BİLGİSİ

Kapak: 1400 kg
Kasa: 500 kg

SİSTEM BİLEŞENLERİ

- Yapısal Kapak
- Yapısal Kasa
- Yüzey Menteşeler
- Hidrolik Kaldırma Silindirleri
- Pençe Kilitler
- Elektrik Kontrol Sistemi
- Pozisyon Sensörleri
- Uzaktan Kumanda

MAIN FEATURES

- W 6640 mm - L 2650 mm Clear Opening
 - ABS / MCA approved
- Surface hinges suitable for teak layer
 - Hydraulic opening / closing
 - Hydraulic claw locks
 - Weathertight design
 - Compression type gasket
- Common power pack serving both hatches
 - Radio remote control
 - 1-minute opening or closing time

MATERIAL INFORMATION

Door: Aluminium
Frame: Stainless Steel
Locks and Hinges: Stainless Steel

WEIGHT INFORMATION

Door: 1400 kg
Frame: 500 kg

SYSTEM COMPONENTS

- Door Construction
- Frame Construction
- Surface Hinges
- Hydraulic Lifting Cylinders
- Hydraulic Claw Locks
- Electric Control System
 - Position Sensors
 - Remote Control